



Palziv Ein Hanatziv M.P. Emek Beit Shean 10805 Israel | www.palziv.com |  
 Tel: +972 46 06 29 99 Fax: +972 46 06 29 58 | contact@palziv.com



Company Number: 570040535

Consol. Busn Number: 557634052

### Product Specification - PA250

Last update: 06/25/10

Desc.	Standard	Value	Unit
Density	ISO 845	250	Kg/m <sup>3</sup>
Tensile strength	ISO 1798	2606	kPa
Elongation	ISO 1798	191	%
Compression 10%	ISO 844	739	kPa
Compression 25%	ISO 844	842	kPa
Compression 50%	ISO 844	1242	kPa
Working Temperature Range	Internal	-60 \ 90	°C
Water Absorption %Vol (max)	Internal	1	%
Shore-A	ASTM D2240	59	A
Shore-OO	ASTM D2240	92	oo

**Palfoam is a closed cell cross-linked polyethylene foam block.**

**Tolerances other than the above may be negotiated.**

**Dimensional stability 24 hr at 70C < 2%.**

**If holes were created during the foaming process, no more than 6 holes of diameter 2mm per 1m<sup>2</sup> sheet are acceptable.**

**This information on Palfoam chemically cross-linked polyethylene foam is presented to the best of our knowledge.**

**Data represents typical values measured on a 10 mm thick specimen and should be considered as guidelines only.**

**PALZIV Kibbutz Ein Hanatziv 10805 Israel. Tel: 972-4-6062999 Fax: 972-4-6062958**

**www.palziv.com Email: contact@palziv.com**